

1.12 NEW DEMINERALISATION UNITS - FOR STREAK FREE GLASSWARE

Description	Dimensions (mm)		Capacity (ltrs)	Part No
	Height	Diameter		
DEMINERALISATION TREATMENT UNIT, 10 LITRE FOR GLASSWASHER, 1040 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	485	200	1040	DM10
DEMINERALISATION TREATMENT UNIT, 18 LITRE FOR GLASSWASHER, 1872 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	545	263	1872	DM20
DEMINERALISATION TREATMENT UNIT, 23 LITRE FOR GLASSWASHER, 2398 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	648	263	2398	DM23
DEMINERALISATION TREATMENT UNIT, 30 LITRE FOR GLASSWASHER, 3100 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	963	263	3100	DM30

1.13 REGENERATED DEMINERALISATION UNITS *Invoiced at New Price. Price listed is final price after credit applied upon return of the expired unit.

Description	Dimensions (mm)		Capacity (ltrs)	Part No
	Height	Diameter		
REGENERATED EXCHANGE DEMINERALISATION TREATMENT UNIT, 10 LITRE FOR GLASSWASHER, 1040 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	485	200	1040	DM10R
REGENERATED EXCHANGE DEMINERALISATION TREATMENT UNIT, 18 LITRE FOR GLASSWASHER, 1872 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	545	263	1872	DM20R
REGENERATED EXCHANGE DEMINERALISATION TREATMENT UNIT, 23 LITRE FOR GLASSWASHER, 2398 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	648	263	2398	DM23R
REGENERATED EXCHANGE DEMINERALISATION TREATMENT UNIT, 30 LITRE FOR GLASSWASHER, 3100 LITRE CAPACITY BASED ON WATER HARDNESS OF 20 ° CLARKE	963	263	3100	DM30R

Granular Activated Carbon - (GAC)

1.14 GRANULAR ACTIVATED CARBON (GAC) DRINKING WATER FILTER

Description	Dimensions (mm)		Capacity (ltrs)	Part No
	Height	Diameter		
GRANULAR ACTIVATED CARBON DRINKING WATER FILTER (3KG CARBON) (5 LITRE VESSEL)	390	170	110000	GAC3
GRANULAR ACTIVATED CARBON DRINKING WATER FILTER (5KG CARBON) (7 LITRE VESSEL)	420	200	177000	GAC5
GRANULAR ACTIVATED CARBON DRINKING WATER FILTER (8KG CARBON) (10 LITRE VESSEL)	485	200	297064	GAC8
GRANULAR ACTIVATED CARBON DRINKING WATER FILTER (12KG CARBON) (15 LITRE)	485	222	384000	GAC12

Each CTU, De-min and GAC is supplied with 3/4" non return valves. Specialist hoses, ball valves and pressure reducing valves can also be supplied. For our full range of water meters, please refer to section 13.

1.15 Accessories

HOSES

Part Number	Dimensions (mm)		Fittings		Description / Application
	Diameter	Length			
EWC-HOSE-0.11-001	DN10	110	3/4" BSP 90'	3/4" BSP STRAIGHT	SHORT METRE TAIL HOSE
EWC-HOSE-1.0-001	DN10	1000	3/4" BSP 90'	3/4" BSP STRAIGHT	10 BORE 1M - USED FOR SOFTENERS AND CTUS
EWC-HOSE-1.5-001	DN10	1500	3/4" BSP 90'	3/4" BSP STRAIGHT	10 BORE 1.5M - SOFTENERS AND CTUS
EWC-HOSE-2.0-001	DN10	2000	3/4" BSP 90'	3/4" BSP STRAIGHT	10 BORE 2M - SOFTENERS AND CTUS

PRESSURE REDUCING VALVES (PRV)

Part Number	Dimensions (mm)		Fittings		Description / Application
	Diameter	Length			
ABB8	-	-	-	-	15MM X 15MM PRV @ 2.8 BAR
WAT82212	-	-	-	-	PRV 3/4" LOOSE NUT @ 3 BAR

WATER METERS

Part Number	Dimensions (mm)		Fittings		Description / Application
	Diameter	Length			
CWMETER1/2	-	-	3/4"	3/4"	CWMETER1/2

CONNECTORS

Item No	Part Number	Dimensions (mm)		Fittings			Description / Application
		Diameter	Length				
1	EWCYSPLIT	3/4"	70MM	3/4"	3/4"	3/4"	PLASTIC T VALVE (ALSO KNOWN AS Y CONNECTOR)

NON-RETURN VALVE - CTU

Item No	Part Number	Dimensions (mm)		Fittings		Description / Application
		DIAMETER	LENGTH			
2	CTUNRVBODY	3/4"	40MM	3/4"	3/4"	BLACK PLASTIC NIPPLE
3	CTUNRV-IN	3/4"	40MM	3/4"	3/4"	PLASTIC NIPPLE WITH NON-RETURN VALVE
	CTUNRV-OUT					
4	CTUNRVBODY-PF	3/4"	40MM	3/4"	3/4"	PLASTIC NIPPLE WITH DM FITTING
5	CTUNRV-PF-IN	3/4"	40MM	3/4"	3/4"	PLASTIC NIPPLE WITH NON-RETURN VALVE AND DM FITTING
	CTUNRV-PF-OUT					

