







INSTALLATION REQUIREMENTS	
MINIMUM WATER PRESSURE	2.0 BAR
MAXIMUM WATER PRESSURE	6.0 BAR
MINIMUM WATER TEMPERATURE	PROTECT FROM FREEZING
MAXIMUM WATER TEMPERATURE	35 deg celsius
CONNECTIONS	3/4" BSP INLET AND OUTLET - OTHER OPTIONS AVAILIABLE UPON REQUEST
CAPACITY (litres)	29858 @ 180 PPM



EUROPEAN WATERCARE LTD REGAL HOUSE, SOUTH ROAD HARLOW, CM20 2BL ESSEX, ENGLAND TEL: +44 (0) 1279 780 250

EUROPEAN WATERCARE LTD
This drawing and its contents are the exclusive property of
European Watercare ltd and may not be used, copied
or disclosed to any third party without the express written
permission of European Watercare ltd. It must be
returned immediately upon request.

APPR. BY:	
APPR. DATE:	
SCALE:	NTS
JOB No:	017
DRAWN BY:	JS
DATE:	06/08/2020
SHEET SIZE:	A4
REV. P	

THIRD ANGLE PROJECTION

TITLE:

DETAIL OF CTU30 - PRIMA HEAD: 2-PORT EUROPEAN WATERCARE

SHEET NUMBER:	1 OF 1
DRAWING No.	CTU PRIMA 30