

ECOSOFT COMMERCIAL REVERSE OSMOSIS SYSTEM MO 12 000

APPLICATION:

Private houses, restaurants, laboratories,
greenhouses, steam generators, carwashes, breweries, bakeries

KEY FEATURES:

- Reliable performance due to high quality of engineering and components
- Saves up to 30% of space* (4 pcs on a pallet)
- Easy-to-use thanks to smart architecture
- Saves up to 50% of energy* due to DOW Filmtec™ XLE membranes and Grundfos pumps
- Original design
- CE marked and confirmed to be safe in accordance with EC New Approach Directives

* As compared to previous models of Ecosoft RO systems

KEY COMPONENTS:

- DOW Filmtec™ XLE-4040 membrane
- Grundfos high pressure pump
- Polypropylene sediment filter, 5-micron, 4.5"x10"
- Ecosoft controller
- Conductivity sensor
- European solenoid valves
- Praher and John Guest fittings/pipes
- Float switch, raw water and permeate pressure switches
- Wooden box packing



ECOSOFT COMMERCIAL REVERSE OSMOSIS SYSTEM MO 12 000

Code	Model	Dimensions, H x W x D, mm (in)	Membranes	Flow capacity**, LPH (GPH)	Pump	Pieces on pallet
M10VCTFWE	MO 12000	1450 x 550 x 400 (57.1 x 21.7 x 15.8)	2/40 x 40	530 (140)	Horizontal multi-stage 0.67 kW/230V	4

** At 25 °C feed water temperature, TDS 1000 mg/L

Maximum feed water TDS is 3000 mg/L