

# ECOSOFT COMMERCIAL REVERSE OSMOSIS SYSTEM MO 36 000

## APPLICATION:

Breweries, pig farms, horse farms, beverages production plants, publishing houses, windows manufacturing, chemical producers, laboratories, greenhouses, steam generators etc.

## KEY FEATURES:

- Reliable performance due to high quality of engineering and components
- Saves up to 50% of space\*
- Easy-to-use thanks to smart architecture
- Saves up to 50% of energy\* due to DOW Filmtec™ XLE membranes and Grundfos pumps
- Original design
- CE marked and confirmed to be safe in accordance with EC New Approach Directives

\* As compared to industrial models of Ecosoft RO

## KEY COMPONENTS:

- DOW Filmtec™ XLE-4040 membrane
- Grundfos high pressure pump
- Polypropylene sediment filter, 5-micron, 4.5"x20"
- Ecosoft controller
- Conductivity sensor
- European solenoid valves
- Praher and John Guest fittings/pipes
- Float switch, raw water and permeate pressure switches
- Wooden box packing



## ECOSOFT COMMERCIAL REVERSE OSMOSIS SYSTEM MO 36 000

Code	Model	Dimensions, H x W x D, mm (in)	Membranes	Flow capacity**, LPH (GPH)	Pump	Pieces on pallet
M36VCTFWE	MO 36000	1500 x 900 x 600 (59.0 x 27.6 x 23.6)	6/40 x 40	1 500 (396)	Horizontal multi-stage 1.9 kW/230V	1

\*\* At 25 °C feed water temperature, TDS 1000 mg/L

Maximum feed water TDS is 3000 mg/L