





The non-electric, high performance water softener.

The AutoSoft+ water softener is a non-electric, high performance system, specially designed for applications where space is limited. In addition to the clever, space-saving design, the softeners are packed with features making them an ideal choice, even when space is not at a premium.

The perfect solution for reducing limescale entering your professional dishwashers and glasswashers. With an innovative twin tank system, the unit can provide a constant stream of softened water with no down times - when regeneration is required, the unit simply switches to the other tank. Compact and effective, the AutoSoft+ helps to reduce down times and maintenance on your warewashing machines. Enjoy prolonged equipment life, more efficient washing and professional results every time.

Applications: Hot or cold fed glasswashers, dishwashers and laundry washing machines



Features & Benefits

- Twin Tank Design Guarantees a continuous and uninterrupted supply of soft water
- Non-Electric Powered by the kinetic energy of moving water
- Metered water use, the system only regenerates when necessary.
- · Cabinet with wheels for easy movement
- Uses soft, conditioned water to self-clean, prolonging the life of the unit
- Economical to use, highly efficient system low salt consumption.
- 100% Recyclable at end of life.
- For use on a hot or cold feed
- 100% Recyclable at end of life

Professional results every time!

Our specialist softeners produce soft water that help produce sparkling clean crockery, cutlery and streak-free glassware. Glasswashers and dishwashers are also protected from the harmful effects of chlorine and scale. Enjoy prolonged equipment life and more efficient washing.

✤ PART CODES, DESCRIPTIONS AND SPECIFICATIONS ON NEXT PAGE

WaterCare | Regal House | South Road | Harlow | Essex | CM20 2BL Tel: 01279 780250 | Email: info@watercare.co.uk | Visit: www.watercare.co.uk





Autosoft+ Technical Specifications

Specifications	
MIN FLOW (L/M)	20
MAX FLOW @ 1 BAR (L/M)	25
SALT CONSUMPTION (KG)	0.5
TIME (MINUTES)	11
VOLUME (LITRES)	34
MEDIA VOLUME (LITRES)	2 x 4.5
SALT CAPACITY (KG)	20
INLET/OUTLET CONNECTIONS	3/4"
MIN PRESSURE (BAR)	1.0
MAX PRESSURE (BAR)	6.0
MIN TEMPERATURE (°C)	2
MAX TEMPERATURE (°C)	65

Part Codes & Descriptions

Description	Dimensions H x W x D (mm)	Capacity (Litres)	Part Code
AUTOSOFT+ WATER SOFTENER	580 x 360 x 360	20 LITRES P/MIN	AUTOSOFT+